

CRISTALLO

IMPULSIÓN DE LÍQUIDOS.

Tubo de PVC plastificado monocapa, para transporte de líquidos.



REF.	TAMAÑO		ESPESOR PARED mm	PESO g/m
	Ø int	Ø ext		
CR0306	3	6	1,5	25
CR0406	4	6	1,0	19
CR0407	4	7	1,5	32
CR0508	5	8	1,5	35
CR0609	6	9	1,5	44
CR0710	7	10	1,5	50
CR0812	8	12	2,0	85
CR1014	10	14	2,0	95
CR1217	12	17	2,5	140
CR1319	13	19	3,0	190
CR1419	14	19	2,5	160
CR1621	16	21,5	3,0	215
CR1825	18	25	3,5	290
CR2027	20	27	3,5	320
CR2230	22	30	4,0	380
CR2534	25	34	4,5	500
CR3040	30	40	5,0	680
CR3545	35	45	5,0	760
CR4050	40	50	5,0	900
CR5060	50	60	5,0	1200

- 
SUPERFÍCIES LISAS

- 
FLEXIBILIDAD

- 
RESISTENCIA A LA ABRASIÓN

- 
TEMPERATURA DE USO
-5° C + 60° C

- 
RESISTENCIA AL APLASTAMIENTO
**

- 
Idóneo según Reg. CE 1935/2004 y Reg. UE 10/2011 al contacto con alimentos que requieren líquidos simulantes del tipo A B C, prueba de migración continua a 40°C por 24 horas.