


M40842


HEMBRA BSP CON O'RING CODO 45° ASIENTO 60° BS5200 / ISO 8436-6 (TUERCA CON PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES				
	DN	Pulgadas	Tamaño		B	A	C	H1	H2
M40892-12-12	19	3/4"	- 12	3/4" - 14	14,5	72,4	8,5	70,0	32
M40892-12-16	19	3/4"	- 12	1" - 11	19,0	72,0	10,6	71,0	41
M40892-16-16	25	1"	- 16	1" - 11	19,5	82,2	10,6	80,5	41
M40892-16-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	95,0	10,1	78,5	50
M40892-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	98,5	10,1	98,0	50
M40892-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	111,5	12,5	109,0	60
M40892-32-32	51	2"	- 32	2" - 11	42,0	143,2	16,1	140,5	70

M42512


HEMBRA JIC ASIENTO 37°—SAE J516/ISO 12151-5 (TUERCA CON PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES				
	DN	Pulgadas	Tamaño		B	A	C	H1	H2
M42512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	36,2	14,2	32	32
M42512-12-16	19	3/4"	- 16	1.5/16" - 12	21,7	33,0	15,2	41	41
M42512-16-16	25	1"	- 16	1.5/16" - 12	21,7	40,7	15,2	41	41
M42512-16-20	25	1"	- 16	1.5/8" - 12	26,0	50,0	16,2	50	50
M42512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	51,4	16,2	50	50
M42512-20-24	31	1.1/4"	- 20	1.7/8" - 12	30,5	54,0	18,8	55	60
M42512-24-24	38	1.1/2"	- 24	1.7/8" - 12	31,0	54,5	18,8	55	60
M42512-32-32	51	2"	- 32	2.1/2" - 12	42,0	54,2	24,0	70	75

M42592

HEMBRA JIC CODO 90° ASIENTO 37°—SAE J516/ISO 12151-5 (TUERCA CON PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES				
	DN	Pulgadas	Tamaño		B	A	C	E	H2
M42592-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	72,4	14,2	66,0	32
M42592-16-16	25	1"	- 16	1.5/16" - 12	21,7	82,3	15,2	77,5	41
M42592-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	98,5	16,2	92,0	50
M42592-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	101,5	18,8	108,0	60
M42592-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	115,5	18,8	106,0	60
M42592-32-32	51	2"	- 32	2.1/2" - 12	42,0	144,7	24,0	137,0	75