


M42542


HEMBRA JIC CODO 45° ASIENTO 37° SAE J516 / ISO 12151-5 (TUERCA CON PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES				
	DN	Pulgadas	Tamaño		T	B	A	C	E
M42542-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	86,0	14,2	33,0	32
M42542-16-16	25	1"	- 16	1.5/16" - 12	21,7	95,0	15,2	37,0	41
M42542-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	115,5	16,2	45,0	50
M42542-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	126,5	18,8	50,0	60
M42542-32-32	51	2"	- 32	2.1/2" - 12	42,0	161,0	24,0	63,5	75

M31210


MACHO MÉTRICO ASIENTO 24°—SERIE PESADA DIN 20066/ ISO 12151-2



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES				
	DN	Pulgadas	Tamaño		T	mm	B	A	C
M31210-10-30	16	5/8"	- 10	M 30x2	20	12,0	36,8	16,0	30
M31210-12-30	19	3/4"	- 12	M 30x2	20	14,5	38,5	16,0	32
M31210-12-36	19	3/4"	- 12	M 36x2	25	14,5	43,4	18,0	36
M31210-16-36	25	1"	- 16	M 36x2	25	19,5	45,0	18,0	36
M31210-16-42	35	1"	- 16	M 42x2	30	19,5	46,8	20,0	46
M31210-20-52	31	1.1/4"	- 20	M 52x2	38	25,0	55,0	22,0	55
M31210-24-52	38	1.1/2"	- 24	M 52x2	38	30,5	55,6	22,0	55


M41613

HEMBRA MÉTRICA O'RING ASIENTO 24° S. PESADA DIN 20066 ISO 12151-2 (TUERCA PASADOR)



M41612

HEMBRA MÉTRICA O'RING ASIENTO 24° S. PESADA DIN 20066 ISO 12151-2 (TUERCA LIBRE)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES			
	DN	Pulgadas	Tamaño		T	mm	B	A
M41613-10-30	16	5/8"	- 10	M 30x2	20	12,0	37,1	3,5
M41612-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	31,0	4,0
M41612-12-30	19	3/4"	- 12	M 30x2	20	12,5	43,9	3,2
M41613-12-36	19	3/4"	- 12	M 36x2	25	14,5	42,1	3,4
M41613-12-42	19	3/4"	- 12	M 42x2	30	19,0	35,8	5,3
M41612-16-36	25	1"	- 16	M 36x2	25	16,0	46,8	4,1
M41613-16-42	25	1"	- 16	M 42x2	30	19,5	46,3	5,3
M41613-16-52	25	1"	- 16	M 52x2	38	26,0	50,5	8,0
M41612-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	47,5	6,1
M41613-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	41,7	8,0
M41612-24-52	38	1.1/2"	- 24	M 52x2	38	29,0	52,5	8,8