



M20542

HEMBRA BSP CODO 45° ASIENTO 60° —BS5200 / ISO12151-6 (TUERCA CON PASADOR)



M20543


HEMBRA BSP CODO 45° ASIENTO 60° —BS5200 / ISO12151-6 (TUERCA LIBRE)



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES				
	DN	Pulgadas	Tamaño		B	A	C	E	H2
M20542-03-02	5	3/16"	- 03	1/8" - 28	3,1	31,0	4,4	15,0	14
M20543-03-04	5	3/16"	- 03	1/4" - 19	4,0	35,5	5,4	14,5	19
M20542-04-02	6	1/4"	- 04	1/8" - 28	3,1	35,5	4,4	14,5	14
M20543-04-04	6	1/4"	- 04	1/4" - 19	4,0	36,0	5,4	15,0	19
M20543-04-06	6	1/4"	- 04	3/8" - 19	7,0	37,5	6,0	16,0	19
M20542-05-04	8	5/16"	- 05	1/4" - 19	4,0	35,5	5,4	16,0	19
M20543-05-06	8	5/16"	- 05	3/8" - 19	7,0	38,0	6,0	13,5	22
M20543-06-06	10	3/8"	- 06	3/8" - 19	7,0	42,0	6,0	15,0	22
M20543-06-08	10	3/8"	- 06	1/2" - 14	9,3	42,5	6,5	16,0	27
M20542-08-06	12	1/2"	- 08	3/8" - 19	7,1	52,0	6,0	20,0	22
M20543-08-08	12	1/2"	- 08	1/2" - 14	9,3	49,5	6,5	17,0	27
M20542-08-10	12	1/2"	- 08	5/8" - 14	12,1	54,5	10,2	22,5	28
M20542-08-12	12	1/2"	- 08	3/4" - 14	15,0	57,0	9,0	25,0	32
M20542-10-10	16	5/8"	- 10	5/8" - 14	12,5	63,0	10,2	26,0	28
M20542-10-12	16	5/8"	- 10	3/4" - 14	15,0	64,0	9,0	27,0	32
M20542-12-08	19	3/4"	- 12	1/2" - 14	9,3	55,5	6,5	22,5	27
M20542-12-12	19	3/4"	- 12	3/4" - 14	15,5	70,5	9,0	28,5	32
M20542-12-16	19	3/4"	- 12	1" - 11	19,8	72,5	10,5	30,0	38
M20542-16-16	25	1"	- 16	1" - 11	19,8	91,0	10,5	36,5	38

M20842

HEMBRA BSP CON O'RING CODO 45° ASIENTO 60° —BS5200 / ISO12151-6 (TUERCA CON PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES				
	DN	Pulgadas	Tamaño		B	A	C	E	H2
M20842-10-10	16	5/8"	- 10	5/8" - 14	12,5	63,5	9,7	27,5	30
M20842-12-12	19	3/4"	- 12	3/4" - 14	15,5	71,0	8,5	29,0	32
M20842-16-12	25	1"	- 16	3/4" - 14	15,0	79,5	8,5	29,0	32
M20842-16-16	25	1"	- 16	1" - 11	19,8	90,5	10,6	35,6	38
M20842-16-20	25	1"	- 16	1.1/4" - 11	26,0	93,0	10,5	38,0	50
M20842-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	101,5	10,5	39,0	50
M20842-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	118,5	12,5	40,5	60
M20842-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	106,5	10,5	42,0	50
M20842-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	118,0	12,5	45,0	60
M20842-32-32	51	2"	- 32	2" - 11	42,0	134,0	16,1	47,0	70