



## M81642

HEMBRA MÉTRICA O'RING CODO 45° AST.24° SER.PESADA DIN 2066 ISO 12151-2 (TUERCA CON PASADOR)



## M81643


HEMBRA MÉTRICA O'RING CODO 45° AST.24° SER.PESADA DIN 2066 ISO 12151-2 (TUERCA LIBRE)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES					
	DN	Pulgadas	Tamaño		T	mm	B	A	C	E
M81642-12-30	19	- 12	3/4"	M 30x2	20	12,5	80	3,2	35	36
M81643-12-36	19	- 12	3/4"	M 36x2	25	14,5	82	3,4	33,5	41
M81642-16-36	25	- 16	1"	M 36x2	25	15	103	4,1	44,5	41
M81643-16-42	25	- 16	1"	M 42x2	30	19,5	94	5,3	36	50
M81642-20-42	31	- 20	1.1/4"	M 42x2	30	19,1	117,5	6	44	50
M81643-20-52	31	- 20	1.1/4"	M 52x2	38	26,1	111	8	40	60

## M72410


MACHO ORFS - SAE J516 / ISO 12151-1



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES			
	DN	Pulgadas	Tamaño		T	B	A	C
M72410-12-12	19	- 12	3/4"	1.3/16" - 12	14,5	41	17	32
M72410-16-16	25	- 16	1"	1.7/16" - 12	19,5	46	17,5	41
M72410-20-20	31	- 20	1.1/4"	1.11/16" - 12	26	50,5	17,5	46
M72410-24-24	38	- 24	1.1/2"	2" - 12	32	53	17,5	55

## M82412

HEMBRA ORFS - SAE J516 / ISO 12151-1



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES				
	DN	Pulgadas	Tamaño		T	B	A	C	H1
M82412-12-12	19	- 12	3/4"	1.3/16" - 12	14,5	38	14,1	32	36
M82412-12-16	19	- 12	3/4"	1.7/16" - 12	19,5	42	15	41	46
M82412-16-16	25	- 16	1"	1.7/16" - 12	19,5	43	15	41	46
M82412-20-20	31	- 20	1.1/4"	1.11/16" - 12	25	52,5	15,1	50	55
M82412-24-24	38	- 24	1.1/2"	2" - 12	30,5	55	15	60	60