


M41693


HEMBRA MÉTRICA O'RING CODO 90° ASIENTO 24° S. PESADA DIN 20066 ISO 12151-2 (TUERCA PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES					
	DN	Pulgadas	Tamaño		T	mm	B	A	C	E
M41693-10-30	16	5/8"	- 10	M 30x2	20	12,0	52,5	3,5	57,5	36
M41693-12-36	19	3/4"	- 12	M 36x2	25	14,5	67,0	3,4	67,5	41
M41693-16-42	25	1"	- 16	M 42x2	30	19,5	81,6	5,3	75,5	50
M41693-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	100,0	8,0	86,5	60

M41643


HEMBRA MÉTRICA O'RING CODO 45° ASIENTO 24° S. PESADA DIN 20066 ISO 12151-2 (TUERCA PASADOR)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES					
	DN	Pulgadas	Tamaño		T	mm	B	A	C	E
M41643-10-30	16	5/8"	- 10	M 30x2	20	12,0	66,5	3,5	29,5	36
M41643-12-36	19	3/4"	- 12	M 36x2	25	14,5	81,0	3,4	33,5	41
M41643-16-42	25	1"	- 16	M 42x2	30	19,5	93,1	5,3	36,0	50
M41643-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	110,0	8,0	40,0	60

M32410


MACHO ORFS - SAE J516 / ISO 12151-1



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES			
	DN	Pulgadas	Tamaño		T	B	A	C
M32410-10-10	16	- 10	5/8"	1" - 14	12	36	15,5	27
M32410-12-12	19	- 12	3/4"	1.3/16" - 12	14,5	40,5	17	32
M32410-12-16	19	- 12	3/4"	1.7/16" - 12	19,8	42,5	17,5	38
M32410-16-16	25	- 16	1"	1.7/16" - 12	19,5	45	17,5	41
M32410-16-20	25	- 16	1"	1.11/16" - 12	25	48	17,5	46
M32410-20-20	31	- 20	1.1/4"	1.11/16" - 12	25	50,5	17,5	46
M32410-24-24	38	- 24	1.1/2"	2" - 12	31	53	17,5	55

M42411

HEMBRA ORFS - SAE J516 / ISO 12151-1 CUELLO LARGO (TUERCA Prensada)



REF.	DIÁMETROS DE MANGUERA			ROSCAS	DIMENSIONES				
	DN	Pulgadas	Tamaño		T	B	A	C	H1
M42411-10-10	16	5/8"	- 10	1" - 14	11,5	39,5	13,5	24	30
M42411-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	45,9	14,5	32	36
M42411-12-16	19	3/4"	- 12	1.7/16" - 12	19,0	46,5	15,0	36	41
M42411-16-12	25	1"	- 16	1.3/16" - 12	14,5	47,5	14,5	38	36
M42411-16-16	25	1"	- 16	1.7/16" - 12	19,5	48,5	15,0	41	41
M42411-16-20	25	1"	- 16	1.11/16" - 12	24,0	48,5	14,8	41	50
M42411-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	54,8	14,8	50	50
M42411-24-24	38	1.1/2"	- 24	2" - 12	31,0	57,8	15,8	60	60