


M83641


BRIDA 6.000 LIBRAS 45° ISO SAE ISO 12151-3 SAE J516



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES			
	DN	Pulgadas	Tamaño		B	A	D	E
M83641-12-12	19	- 12	3/4"	3/4"	16	81,5	41,4	28
M83641-12-16	19	- 12	3/4"	1"	19,5	85,5	47,7	32,5
M83641-16-12	25	- 16	1"	3/4"	16	87,5	41,4	28
M83641-16-16	25	- 16	1"	1"	19,5	92	47,7	32,5
M83641-16-20	25	- 16	1"	1.1/4"	26	97	54,2	37
M83641-20-16	31	- 20	1.1/4"	1"	19,5	95,5	47,7	31,5
M83641-20-20	31	- 20	1.1/4"	1.1/4"	26	96,5	54,2	38
M83641-20-24	31	- 20	1.1/4"	1.1/2"	32	104,5	63,7	44,5
M83641-24-20	38	- 24	1.1/2"	1.1/4"	26	110,5	54,2	38
M83641-24-24	38	- 24	1.1/2"	1.1/2"	32	109,5	63,7	44
M83641-24-32	38	- 24	1.1/2"	2"	42	121,5	79,6	56
M83641-32-32	51	- 32	2"	2"	42	148	79,6	59

M83911

BRIDA RECTA SUPERCAT



REF.	DIÁMETROS DE MANGUERA			ROSCAS T	DIMENSIONES			
	DN	Pulgadas	Tamaño		B	A	D	S
M83911-12-12	19	- 12	3/4"	3/4"	14,5	75	41,5	14,3
M83911-12-16	19	- 12	3/4"	1"	19,5	80,5	47,7	14,3
M83911-16-16	25	- 16	1"	1"	19,5	80	47,7	14,3
M83911-16-20	25	- 16	1"	1.1/4"	26	84	54	14,3
M83911-20-20	31	- 20	1.1/4"	1.1/4"	26	80,5	54	14,3
M83911-20-24	31	- 20	1.1/4"	1.1/2"	32	84	63,6	14,3
M83911-24-24	38	- 24	1.1/2"	1.1/2"	32	84,5	63,6	14,3
M83911-24-32	38	- 24	1.1/2"	2"	42	107,5	79,3	14,3
M83911-32-24	51	- 32	2"	1.1/2"	32	95,5	63,6	14,3
M83911-32-32	51	- 32	2"	2"	42	110,5	79,3	14,3