

CUTTING MACHINES

M30 CUT L

STARTER AND PROFESSIONAL WORKSHOP

STAND TYPE CUTTING MACHINE



KEY ADVANTAGES

- Compact design
- Easy and safe to use
- Versatile, scalloped blade for high performance and efficient cutting with minimal smoke
- Ergonomic, easy to clean
- Integrated dust collector

MAIN APPLICATIONS

Benchtop machine for after-market service, container workshop or mobile van service, field repair and intermittent service workshops.

TECHNICAL SPECIFICATIONS

Dimensions:	765 x 500 x 1150 mm (30 x 20 x 45")	Motor:	3.0 kW
Net Weight:	92 kg (203 lb)	Rotation Speed:	3000 rpm
Packaging:	800 x 600 x 1200 mm (32 x 24 x 47")	Scalloped Blade Diameter:	254 mm (10")
Gross Weight:	120 kg (265 lb)	Max. Hose OD:	85 mm (3.34")
Voltages:	220/240 V, 3Ph, 50 Hz 380/415 V, 3Ph, 50 Hz 208/240 V, 3Ph, 60 Hz 380/415 V, 3Ph, 60 Hz		
Capacity:	2wb: 2" max. 4ws: 2" max. 6ws: 1 1/4" max. Industrial: 2"		

HOSE AND FITTING SELECTION

Hose Type	Max. Hose Size	Ref. Hoses
2 Wire Braid & Textile	2"	Tractor; Harvester; Lyteflex; Pilot; Cover; Equator; Rockmaster (braided); Shieldmaster (braided); Astro; Multitex; Hydroplast; Spirtex/K
4 Wire Spirals	2"	Rockmaster (spiral); Shieldmaster (spiral); GoldenISO Xtraflex; Goldenblast
6 Wire Spirals	1 1/4"	Rockmaster/13; Rockmaster/15; Diamondspir



Performances measured on a 400 V, 3Ph, 50 Hz network

CUTTING MACHINES

M30 CUT L

STARTER AND PROFESSIONAL WORKSHOP

STAND TYPE CUTTING MACHINE

ORDERING INFORMATION

Product Code	Description
EOC3424NM30CUTL	M30 CUT L 380/415V 3PH 50HZ
EOC3427NM30CUTL	M30 CUT L 220/240V 3PH 50HZ

AVAILABLE ACCESSORIES

Product Code	Description
3015309	Cutting Disc Scalloped Style 250 mm
ESC3440NCRL2M	Cutting Rail Length 2 M
ESC3440NCRL3M	Cutting Rail Length 3 M
ESC3440NJUCUR	Junction for Cutting Rail