


VÁLVULA ESFERA DOS PIEZAS PASO TOTAL

HEMBRA HEMBRA



| Ref | Ø | D mm. | L mm. | L2 mm. | H mm. |
|-----------|--------|-------|-------|--------|-------|
| X25806004 | 1/4v | 12 | 48 | 103 | 45 |
| X25806006 | 3/8v | 12,5 | 55 | 103 | 45 |
| X25806008 | 1/2v | 15 | 58 | 100 | 47 |
| X25806012 | 3/4v | 20 | 65 | 115 | 56 |
| X25806016 | 1" | 25 | 78 | 130 | 62 |
| X25806020 | 1 1/4v | 32 | 90 | 155 | 74 |
| X25806024 | 1 1/2v | 38 | 102 | 155 | 78 |
| X25806032 | 2" | 50 | 122 | 180 | 96 |
| X25806040 | 2 1/2v | 65 | 138 | 250 | 125 |
| X25806048 | 3" | 76 | 164 | 250 | 135,5 |
| X25806056 | 4" | 94 | 218 | 318 | 165 |

Cuerpo en acero inoxidable CF8M (AISI 316).

Eje en AISI 316.

Maneta en AISI 304 recubierta en PVC azul.

Asiento de la bola PTFE + 15% GF.

Extremos rosca ISO 7/1

Temperatura de trabajo de -20° C a 220° C.

Presión de trabajo 1000 WOG / PN 63

Sistema de bloqueo.